Report No.: Test Time: 2025-04-17 17:04

Luminaire Property

Luminaire Manufacturer:
Luminaire Category:
Luminaire Description: CFWG2455R-7W-3000K-25°
Lamp Catalog: Lamp Description:
Number of Lamps: Lumens per Lamp:
Luminous Length (mm): -50 Luminous Width (mm): -50
Luminous Height (mm): Voltage: 220.19 V
Current: 0.0550 A Power: 6.49 W
Power Factor: 0.5330

Photometric Results

CIE Class: Direct Total Rated Lamp Lumens: 408.7 lm
Measurement Flux: 408.7 lm Efficiency: 100%
Downward Ratio: 100% Upward Ratio: 0%
Horizontal Diffuse Angle(50%): H25.3
Vertical Diffuse Angle(50%): V25.6
Luminous Efficacy (lm/w): 62.98 C0r0 Intensity: 2015.7 cd
Max. Intensity: 2025.82 cd Pos of Max. Intensity: H180 V1
S/MH(C0/C180): 0.43 S/MH(C90/C270): 0.44

Picture Of Luminaire

Luminous Intensity Distribution Curve



Unit: cd
Average Diffuse Angle(50%): 25.4°
C0-C180 C90-C270

C Plane (°):0.0-360.0: 90.0 Gamma Plane (°):0.0-180.0:1.0
Test Lab: Test Device: GPM-1600L
Test Type: TYPE C Distance: 9.904 m [K=1.0000]
Temperature: Humidity:
Operator: Inspector:

Luminous Intensity Distribution Curve





C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1	1.15	1.13	1.11	1.10	1.13	1.11	1.10	1.08	1.07	1.06	1.05	1.04	1.03	1.02	1.00	0.99	0.99	0.97
2	1.12	1.08	1.06	1.03	1.10	1.07	1.04	1.02	1.04	1.02	1.00	1.01	0.99	0.98	0.98	0.97	0.96	0.94
3	1.09	1.04	1.01	0.98	1.07	1.03	1.00	0.97	1.00	0.98	0.96	0.98	0.96	0.94	0.96	0.94	0.93	0.92
4	1.05	1.00	0.97	0.94	1.04	0.99	0.96	0.93	0.97	0.95	0.92	0.96	0.93	0.91	0.94	0.92	0.90	0.89
5	1.03	0.97	0.93	0.90	1.01	0.96	0.93	0.90	0.95	0.92	0.89	0.93	0.91	0.89	0.92	0.90	0.88	0.87
6	1.00	0.94	0.90	0.87	0.99	0.93	0.90	0.87	0.92	0.89	0.87	0.91	0.88	0.86	0.90	0.87	0.86	0.85
7	0.97	0.91	0.88	0.85	0.96	0.91	0.87	0.85	0.90	0.87	0.84	0.89	0.86	0.84	0.88	0.85	0.83	0.82
8	0.95	0.89	0.85	0.82	0.94	0.88	0.85	0.82	0.88	0.84	0.82	0.87	0.84	0.82	0.86	0.83	0.81	0.80
9	0.93	0.87	0.83	0.80	0.92	0.86	0.83	0.80	0.85	0.82	0.80	0.85	0.82	0.80	0.84	0.81	0.79	0.79
10	0.91	0.84	0.81	0.78	0.90	0.84	0.81	0.78	0.83	0.80	0.78	0.83	0.80	0.78	0.82	0.80	0.78	0.77

Spacing Criteria (0-180): 0.43
Spacing Criteria (90-270): 0.44
Spacing Criteria (Diagonal): 0.41

Curves of Luminaires vs Lighting Area



C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

IsoLux Plot



Mounting Height: 10.0m Max Lux(100%): 20.2 lx

(1%): 0.2 lx	(2%): 0.4 lx
(5%): 1.0 lx	(10%): 2.0 lx
(20%): 4.0 lx	(50%): 10.1 lx
(100%): 20.2 lx	

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h





L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	346	166	124	0	0	0	0	0	0
C90	591	436	240	0	0	0	0	0	0
C180	886	491	302	0	0	0	0	0	0
C270	540	111	124	143	0	0	138	0	0

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Illuminance at a Distance



Dist(m)	Enadir(lx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(lx)
1.0	2015.70	0.45/0.45	0.2	884.70
2.0	503.92	0.90/0.91	0.6	221.17
3.0	223.97	1.34/1.36	1.5	98.30
4.0	125.98	1.79/1.82	2.6	55.29
5.0	80.63	2.24/2.27	4.1	35.39

Beam Angle(B): H25.3 V25.6 Field Angle(F): H40.6 V40.7

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 2015.7 lx

(1%): 20.2 lx
(2%): 40.3 lx
(5%): 100.8 lx
(10%): 201.6 lx
(20%): 403.1 lx
(50%):1007.8 lx
(100%):2015.7 lx

C Plane (°):0.0-360.0: 90.0
Gamma Plane (°):0.0-180.0:1.0
Test Lab:
Test Device: GPM-1600L
Test Type: TYPE C
Distance: 9.904 m [K=1.0000]
Temperature:
Humidity:
Operator:
Inspector:

Area Flux Table

Unit: lm

Horizontal plane	Vertical plane																							
	-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	Flux(T)	Flux(E)
-90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.2	0.0
-40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.1	0.0
-30	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	10.8	1.4
-20	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	62.9	55.2
-10	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	146.9	140.7
0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	134.4	127.9
10	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	43.4	34.1
20	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7	0.0
30	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0	0.0
40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.0
50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90																				408	
Flux(T)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0		359
Flux(E)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	359	

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

The Average Illuminance Effective Figure



C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	2.2	2.7	2.4	2.9	3.1	4.0	4.5	4.2	4.7	4.9
3H	2.0	2.5	2.3	2.8	3.0	3.8	4.3	4.1	4.6	4.8
4H	2.0	2.4	2.2	2.7	2.9	3.8	4.2	4.1	4.5	4.7
6H	1.9	2.3	2.2	2.6	2.9	3.7	4.1	4.0	4.4	4.7
8H	1.8	2.3	2.2	2.6	2.9	3.6	4.1	4.0	4.4	4.7
12H	1.8	2.2	2.1	2.5	2.8	3.6	4.0	3.9	4.3	4.6
X=4H Y=2H	2.0	2.4	2.2	2.7	2.9	3.8	4.2	4.0	4.5	4.7
3H	1.8	2.2	2.1	2.5	2.8	3.6	4.0	3.9	4.3	4.6
4H	1.7	2.1	2.1	2.4	2.8	3.5	3.9	3.9	4.2	4.6
6H	1.6	2.0	2.0	2.3	2.7	3.4	3.8	3.8	4.1	4.5
8H	1.6	1.9	2.0	2.3	2.7	3.4	3.7	3.8	4.1	4.5
12H	1.5	1.8	2.0	2.2	2.6	3.3	3.6	3.8	4.0	4.4
X=8H Y=4H	1.6	1.9	2.0	2.3	2.7	3.4	3.7	3.8	4.1	4.5
6H	1.5	1.7	1.9	2.1	2.6	3.3	3.5	3.7	3.9	4.4
8H	1.4	1.6	1.9	2.1	2.6	3.2	3.4	3.7	3.9	4.4
12H	1.4	1.6	1.8	2.0	2.5	3.2	3.4	3.7	3.8	4.3
X=12H Y=4H	1.5	1.8	2.0	2.2	2.6	3.3	3.6	3.8	4.0	4.4
6H	1.4	1.6	1.9	2.1	2.6	3.2	3.4	3.7	3.9	4.4
8H	1.4	1.6	1.8	2.0	2.5	3.2	3.4	3.7	3.8	4.3
Variations with the observer position at spacings:										
S=1.0H	+6.7/-19.5					+6.4/-23.9				
S=1.5H	+9.6/-46.8					+9.2/-29.5				
S=2.0H	+11.6/-1.$					+11.2/-1.$				

Calculate in accordance with CIE Pub.117. The table is revised with 409lm (8log(F/F0) = -3.1).

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM



ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	186	45.4
FL (0°-30°)	181	44.2
FM (30°-60°)	5	1.2
FH (60°-80°)	0	0.0
FVH (80°-90°)	0	0.0
BACK LIGHT	223	54.6
BL (0°-30°)	216	52.8
BM (30°-60°)	7	1.8
BH (60°-80°)	0	0.0
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(**B**acklight,**U**plight,**G**lare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U0 G0

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 0.50								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.99	1.03	1.06	1.08	1.10	1.12	1.13	1.15	1.16
	0.30		0.95	1.00	1.03	1.05	1.08	1.10	1.11	1.13	1.15
	0.20		0.93	0.97	1.00	1.02	1.06	1.08	1.09	1.12	1.13
0.50	0.50	0.20	0.98	1.01	1.04	1.05	1.08	1.09	1.10	1.11	1.12
	0.30		0.95	0.99	1.01	1.03	1.06	1.07	1.08	1.10	1.11
	0.20		0.92	0.96	0.99	1.01	1.04	1.06	1.07	1.09	1.10
0.30	0.50	0.20	0.97	1.00	1.02	1.03	1.05	1.06	1.07	1.08	1.08
	0.30		0.94	0.97	1.00	1.01	1.03	1.05	1.05	1.07	1.07
	0.20		0.92	0.96	0.98	1.00	1.02	1.03	1.04	1.06	1.07
0.00	0.00	0.00	0.91	0.94	0.96	0.97	0.99	1.00	1.00	1.01	1.02

Rating:6W Photometrically tested without ceiling board.

Multiply UF values by service correction factors

Calculate in accordance with CIBSE Technical Memorandum NO.5 1980

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 0.50								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.43	0.35	0.30	0.26	0.20	0.17	0.15	0.11	0.09
	0.30		0.36	0.30	0.26	0.23	0.19	0.16	0.14	0.11	0.09
	0.20		0.31	0.26	0.23	0.20	0.17	0.14	0.13	0.10	0.08
0.50	0.50	0.20	0.40	0.32	0.27	0.24	0.19	0.20	0.13	0.10	0.08
	0.30		0.34	0.28	0.24	0.21	0.17	0.14	0.12	0.10	0.08
	0.20		0.30	0.25	0.22	0.19	0.16	0.13	0.12	0.09	0.08
0.30	0.50	0.20	0.38	0.30	0.25	0.22	0.17	0.14	0.12	0.09	0.07
	0.30		0.33	0.27	0.23	0.20	0.16	0.13	0.11	0.09	0.07
	0.20		0.29	0.24	0.20	0.18	0.14	0.12	0.10	0.08	0.07
0.00	0.00	0.00	0.13	0.10	0.08	0.07	0.05	0.04	0.03	0.03	0.02

Rating:6W Photometrically tested without ceiling board.

Multiply UF values by service correction factors

Calculate in accordance with CIBSE Technical Memorandum NO.5 1980

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 0.50								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.12	0.14	0.15	0.16	0.18	0.19	0.19	0.21	0.21
	0.30		0.09	0.11	0.13	0.14	0.16	0.17	0.18	0.19	0.20
	0.20		0.07	0.09	0.11	0.12	0.14	0.15	0.17	0.18	0.19
0.50	0.50	0.20	0.11	0.13	0.14	0.16	0.17	0.18	0.19	0.20	0.20
	0.30		0.09	0.11	0.12	0.13	0.15	0.16	0.17	0.19	0.19
	0.20		0.07	0.09	0.10	0.12	0.14	0.15	0.16	0.18	0.18
0.30	0.50	0.20	0.11	0.13	0.14	0.15	0.16	0.17	0.18	0.19	0.19
	0.30		0.08	0.10	0.12	0.13	0.15	0.16	0.17	0.18	0.19
	0.20		0.07	0.09	0.10	0.12	0.13	0.15	0.16	0.17	0.18
0.00	0.00	0.00	NA	NA	NA	NA	NA	NA	NA	NA	NA

Rating:6W Photometrically tested without ceiling board.

Multiply UF values by service correction factors

Calculate in accordance with CIBSE Technical Memorandum NO.5 1980

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C90.0	C180.0	C270.0	C360.0					
G0.0	2015.7	2004.8	2015.7	2004.8	2015.7					
G1.0	1989.7	1978.3	2025.8	2018.5	1989.7					
G2.0	1954.3	1942.7	2024.5	2020.6	1954.3					
G3.0	1898.3	1887.2	2009.2	2010.7	1898.3					
G4.0	1836.3	1826.0	1983.4	1989.2	1836.3					
G5.0	1762.0	1751.7	1942.8	1958.0	1762.0					
G6.0	1666.7	1655.3	1887.4	1911.9	1666.7					
G7.0	1566.6	1547.2	1822.8	1855.3	1566.6					
G8.0	1449.3	1430.3	1734.9	1782.8	1449.3					
G9.0	1315.6	1292.2	1645.1	1704.7	1315.6					
G10.0	1186.1	1151.7	1542.7	1609.9	1186.1					
G11.0	1040.7	1000.7	1414.1	1490.3	1040.7					
G12.0	905.6	861.8	1293.1	1373.0	905.6					
G13.0	767.0	721.4	1147.8	1234.4	767.0					
G14.0	629.7	584.1	1019.2	1096.0	629.7					
G15.0	509.1	472.4	884.1	963.1	509.1					
G16.0	407.6	374.7	745.2	811.6	407.6					
G17.0	314.8	287.7	620.6	685.7	314.8					
G18.0	243.6	222.3	511.0	568.1	243.6					
G19.0	186.5	170.9	401.0	447.8	186.5					
G20.0	147.1	135.2	320.7	354.0	147.1					
G21.0	118.1	110.6	246.1	273.3	118.1					
G22.0	94.5	90.5	195.2	214.6	94.5					
G23.0	79.1	76.6	154.4	167.0	79.1					
G24.0	67.3	65.1	123.7	131.1	67.3					
G25.0	56.9	55.8	102.9	106.2	56.9					
G26.0	49.7	48.7	86.9	87.9	49.7					
G27.0	43.2	42.1	73.0	72.6	43.2					
G28.0	38.2	36.9	63.0	62.3	38.2					
G29.0	33.5	32.3	54.6	53.3	33.5					
G30.0	29.1	27.7	48.2	46.7	29.1					
G31.0	25.2	23.7	42.5	41.4	25.2					
G32.0	21.3	19.9	37.3	36.1	21.3					
G33.0	17.4	15.7	32.7	32.0	17.4					
G34.0	13.4	11.4	28.9	28.0	13.4					
G35.0	9.4	7.6	24.6	24.1	9.4					
G36.0	6.8	5.8	20.8	20.3	6.8					

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C90.0	C180.0	C270.0	C360.0					
G37.0	4.6	4.4	16.5	15.7	4.6					
G38.0	2.9	3.3	12.3	11.9	2.9					
G39.0	1.8	2.6	9.1	8.4	1.8					
G40.0	1.1	1.7	6.6	5.5	1.1					
G41.0	1.0	1.4	4.7	3.7	1.0					
G42.0	0.8	1.2	3.4	2.3	0.8					
G43.0	0.8	1.0	2.3	1.4	0.8					
G44.0	0.6	1.0	1.5	1.0	0.6					
G45.0	0.5	0.8	1.2	0.8	0.5					
G46.0	0.3	0.7	1.0	0.6	0.3					
G47.0	0.3	0.7	0.9	0.6	0.3					
G48.0	0.3	0.6	0.8	0.3	0.3					
G49.0	0.2	0.6	0.7	0.3	0.2					
G50.0	0.2	0.6	0.6	0.1	0.2					
G51.0	0.1	0.5	0.6	0.3	0.1					
G52.0	0.1	0.4	0.5	0.2	0.1					
G53.0	0.1	0.3	0.3	0.1	0.1					
G54.0	0.1	0.4	0.3	0.1	0.1					
G55.0	0.1	0.3	0.3	0.1	0.1					
G56.0	0.1	0.1	0.3	0.1	0.1					
G57.0	0.1	0.1	0.2	0.2	0.1					
G58.0	0.0	0.1	0.1	0.1	0.0					
G59.0	0.0	0.0	0.1	0.1	0.0					
G60.0	0.0	0.0	0.0	0.1	0.0					
G61.0	0.0	0.0	0.1	0.1	0.0					
G62.0	0.0	0.0	0.0	0.0	0.0					
G63.0	0.0	0.0	0.0	0.1	0.0					
G64.0	0.0	0.0	0.0	0.0	0.0					
G65.0	0.0	0.0	0.0	0.0	0.0					
G66.0	0.0	0.0	0.0	0.0	0.0					
G67.0	0.0	0.0	0.0	0.0	0.0					
G68.0	0.0	0.0	0.0	0.0	0.0					
G69.0	0.0	0.0	0.0	0.0	0.0					
G70.0	0.0	0.0	0.0	0.0	0.0					
G71.0	0.0	0.1	0.0	0.1	0.0					
G72.0	0.0	0.0	0.0	0.0	0.0					
G73.0	0.0	0.0	0.0	0.0	0.0					

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Candlepower Table (Continue 2)

Unit: cd

G\C	C0.0	C90.0	C180.0	C270.0	C360.0					
G74.0	0.0	0.0	0.0	0.0	0.0					
G75.0	0.0	0.0	0.0	0.1	0.0					
G76.0	0.0	0.0	0.0	0.0	0.0					
G77.0	0.0	0.0	0.0	0.0	0.0					
G78.0	0.0	0.0	0.0	0.0	0.0					
G79.0	0.0	0.0	0.0	0.0	0.0					
G80.0	0.0	0.0	0.0	0.0	0.0					
G81.0	0.0	0.0	0.0	0.0	0.0					
G82.0	0.0	0.0	0.0	0.0	0.0					
G83.0	0.0	0.0	0.0	0.0	0.0					
G84.0	0.0	0.0	0.0	0.0	0.0					
G85.0	0.0	0.0	0.0	0.0	0.0					
G86.0	0.0	0.0	0.0	0.0	0.0					
G87.0	0.0	0.0	0.0	0.0	0.0					
G88.0	0.0	0.0	0.0	0.0	0.0					
G89.0	0.0	0.0	0.0	0.0	0.0					
G90.0	0.0	0.0	0.0	0.0	0.0					
G91.0	0.0	0.0	0.0	0.0	0.0					
G92.0	0.0	0.0	0.0	0.0	0.0					
G93.0	0.0	0.0	0.0	0.0	0.0					
G94.0	0.0	0.0	0.0	0.0	0.0					
G95.0	0.0	0.0	0.0	0.0	0.0					
G96.0	0.0	0.0	0.0	0.0	0.0					
G97.0	0.0	0.0	0.0	0.0	0.0					
G98.0	0.0	0.0	0.0	0.0	0.0					
G99.0	0.0	0.0	0.0	0.0	0.0					
G100.0	0.0	0.0	0.0	0.0	0.0					
G101.0	0.0	0.0	0.0	0.0	0.0					
G102.0	0.0	0.0	0.0	0.0	0.0					
G103.0	0.0	0.0	0.0	0.0	0.0					
G104.0	0.0	0.0	0.0	0.0	0.0					
G105.0	0.0	0.0	0.0	0.0	0.0					
G106.0	0.0	0.0	0.0	0.0	0.0					
G107.0	0.0	0.0	0.0	0.0	0.0					
G108.0	0.0	0.0	0.0	0.0	0.0					
G109.0	0.0	0.0	0.0	0.0	0.0					
G110.0	0.0	0.0	0.0	0.0	0.0					

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Candlepower Table (Continue 3)

Unit: cd

G\C	C0.0	C90.0	C180.0	C270.0	C360.0					
G111.0	0.0	0.0	0.0	0.0	0.0					
G112.0	0.0	0.0	0.0	0.0	0.0					
G113.0	0.0	0.0	0.0	0.0	0.0					
G114.0	0.0	0.0	0.0	0.0	0.0					
G115.0	0.0	0.0	0.0	0.0	0.0					
G116.0	0.0	0.0	0.0	0.0	0.0					
G117.0	0.0	0.0	0.0	0.0	0.0					
G118.0	0.0	0.0	0.0	0.0	0.0					
G119.0	0.0	0.0	0.0	0.0	0.0					
G120.0	0.0	0.0	0.0	0.0	0.0					
G121.0	0.0	0.0	0.0	0.0	0.0					
G122.0	0.0	0.0	0.0	0.0	0.0					
G123.0	0.0	0.0	0.0	0.0	0.0					
G124.0	0.0	0.0	0.0	0.0	0.0					
G125.0	0.0	0.0	0.0	0.0	0.0					
G126.0	0.0	0.0	0.0	0.0	0.0					
G127.0	0.0	0.0	0.0	0.0	0.0					
G128.0	0.0	0.0	0.0	0.0	0.0					
G129.0	0.0	0.0	0.0	0.0	0.0					
G130.0	0.0	0.0	0.0	0.0	0.0					
G131.0	0.0	0.0	0.0	0.0	0.0					
G132.0	0.0	0.0	0.0	0.0	0.0					
G133.0	0.0	0.0	0.0	0.0	0.0					
G134.0	0.0	0.0	0.0	0.0	0.0					
G135.0	0.0	0.0	0.0	0.0	0.0					
G136.0	0.0	0.0	0.0	0.0	0.0					
G137.0	0.0	0.0	0.0	0.0	0.0					
G138.0	0.0	0.0	0.0	0.0	0.0					
G139.0	0.0	0.0	0.0	0.0	0.0					
G140.0	0.0	0.0	0.0	0.0	0.0					
G141.0	0.0	0.0	0.0	0.0	0.0					
G142.0	0.0	0.0	0.0	0.0	0.0					
G143.0	0.0	0.0	0.0	0.0	0.0					
G144.0	0.0	0.0	0.0	0.0	0.0					
G145.0	0.0	0.0	0.0	0.0	0.0					
G146.0	0.0	0.0	0.0	0.0	0.0					
G147.0	0.0	0.0	0.0	0.0	0.0					

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector:

Candlepower Table (Continue 4)

Unit: cd

G\C	C0.0	C90.0	C180.0	C270.0	C360.0					
G148.0	0.0	0.0	0.0	0.0	0.0					
G149.0	0.0	0.0	0.0	0.0	0.0					
G150.0	0.0	0.0	0.0	0.0	0.0					
G151.0	0.0	0.0	0.0	0.0	0.0					
G152.0	0.0	0.0	0.0	0.0	0.0					
G153.0	0.0	0.0	0.0	0.0	0.0					
G154.0	0.0	0.0	0.0	0.0	0.0					
G155.0	0.0	0.0	0.0	0.0	0.0					
G156.0	0.0	0.0	0.0	0.0	0.0					
G157.0	0.0	0.0	0.0	0.0	0.0					
G158.0	0.0	0.0	0.0	0.0	0.0					
G159.0	0.0	0.0	0.0	0.0	0.0					
G160.0	0.0	0.0	0.0	0.0	0.0					
G161.0	0.0	0.0	0.0	0.0	0.0					
G162.0	0.0	0.0	0.0	0.0	0.0					
G163.0	0.0	0.0	0.0	0.0	0.0					
G164.0	0.0	0.0	0.0	0.0	0.0					
G165.0	0.0	0.0	0.0	0.0	0.0					
G166.0	0.0	0.0	0.0	0.0	0.0					
G167.0	0.0	0.0	0.0	0.0	0.0					
G168.0	0.0	0.0	0.0	0.0	0.0					
G169.0	0.0	0.0	0.0	0.0	0.0					
G170.0	0.0	0.0	0.0	0.0	0.0					
G171.0	0.0	0.0	0.0	0.0	0.0					
G172.0	0.0	0.0	0.0	0.0	0.0					
G173.0	0.0	0.0	0.0	0.0	0.0					
G174.0	0.0	0.0	0.0	0.0	0.0					
G175.0	0.0	0.0	0.0	0.0	0.0					
G176.0	0.0	0.0	0.0	0.0	0.0					
G177.0	0.0	0.0	0.0	0.0	0.0					
G178.0	0.0	0.0	0.0	0.0	0.0					
G179.0	0.0	0.0	0.0	0.0	0.0					
G180.0	0.0	0.0	0.0	0.0	0.0					

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 9.904 m [K=1.0000]
Humidity:
Inspector: